

# CLEARFLOW™ HOSES

CLEARLY A BETTER HOSE



ClearFlow™ hoses offer the latest technology in adhesive heating and insulation to lengthen the life of your hose. The newly insulated jacket will keep a steady, consistent temperature improving adhesive flow and reducing charring and curing.

## BENEFITS:

- ❖ Updated insulation to support high performance, demanding and variable environments.
- ❖ Nylon filled fiberglass cuffs that improve durability of the hose connection
- ❖ Hose connector is compatible with many standard hot melt adhesive systems
- ❖ Heat flow technology will reduce long term charring and damage to the interior of the hose, making it last up to twice as long.
- ❖ Longer usage life, reduces downtime and maintenance costs.
- ❖ Less charring will result in fewer nozzle clogs, lengthening the life of your nozzles and reducing cleaning time.

## SPECIFICATIONS

**Maximum Operating Temperature:**  
450 °F (232 °C)

**Maximum Operating Pressure:**  
1500 psi (10.34 MPa)

**Electrical Specifications:** 200 – 240  
VAC 50/60 Hz

**Maximum Bend Radius:** 5 inches

**Available Lengths:** 2 – 24 ft.  
(Custom lengths available)

**Available Types:** Hi-Flex, Water  
Resistant, Hand Gun

## INLINE FILTERS

### STRAIGHT



### 45 DEGREE



### 90 DEGREE



# CLEARFLOW™ WATERWASH HOSES

CLEARLY A BETTER HOSE



ClearFlow™ waterwash hoses offer the same benefits as our standard ClearFlow™ hoses, but with a secure waterwash connection between hose and glue head. All ClearFlow™ waterwash hoses are encased with state of the art, high temperature, extremely durable, waterproof jacketing.



For more information, contact us directly:

Sales:  
Meredith Jenners  
[meredith@ussefl.com](mailto:meredith@ussefl.com)  
(800) 848-5018 x331

Technical Support:  
Chris Rappolt  
[chris@ussefl.com](mailto:chris@ussefl.com)  
(800) 848-5018 x334

Find us on:



## SPECIFICATIONS

**Maximum Operating Temperature:**  
450 °F (232 °C)

**Maximum Operating Pressure:**  
1500 psi (10.34 MPa)

**Electrical Specifications:** 200 – 240  
VAC 50/60 Hz

**Maximum Bend Radius:** 5 inches

**Available Lengths:** 2 – 24 ft.  
(Custom lengths available)